

Heavy Duty Multi-Blade Rip Saw

OUTSTANDING FEATURES:

- Exclusively designed lubricator provides excellent lubrication performance.
- The link chain features no gap running for added safety protection.
- Eccentric adjustment of spindle.
- Complete safety guard for standard machine.
- 3 rows anti-kickback fingers at infeed end.
- Powered elevation of pressure mechanism is optional.
- Wide range variable feed speed 6.7 to 35 m/min
- Ruggedly constructed throughout for maximum stability of operation.
- Precision saw arbor gives accurate and smooth cut.



Small Pressure Plate

- The small wood pressure plate is applied when cutting thick workpieces. The large and small pressure plates are easy to change.



Variable Feed Speed

- The wide range of feed speeds (6.7 to 35 meters per minute) make the machine ideal for cutting all types of wood material. Front mounted speed regulation wheel provides operation convenience.



Newly Designed Link Chain

- The special link chain features no-gap running, which prevents the dangers of operator's hands being clamped and chips falling into the machine. The link chain is manufactured from durable cast iron, providing high breaking strength over 24000 kgs.
- The feed rail is manufactured from alloy steel, hardened to over HRC 50 degrees for maximum durability and wear resistance.



Comprehensive Anti-Kickback Fingers

- The machine is equipped with 3 rows of anti-kickback fingers at the infeed end, combined with a side guard, providing comprehensive safety protection for the operator during operation.



Large Pressure Plate

- The specially designed large wood pressure plate holds workpiece firmly for maximum cutting stability. The large pressure plate is especially ideal for cutting short workpieces.



Automatic power off

- When any guard cover is opened, the power shuts off automatically for safety.



HM14-6
HM14-2

SPECIFICATIONS

Straight Line Rip Saw

	HM12	HM16	HR-18 / HR-20
Model No.	200-1620	200-2520	200-1720
Max. depth of cut	250	250	400 (16")
Max sawblade diameter	300	375	425
Useful length of sawblade bush	300	300	300
Width of feed chain	300	300	300
Power of saw motor	Standard	Standard	Standard
Feed motor	Standard	Standard	Standard
Speed of saw arbor	Standard	Standard	Standard
Variable feed speed of chain	Standard	Standard	Standard
Net weight	400	400	300
Packing weight	400	400	400
Packing dimensions (L x W x H)	1200	1200	1700 (HR-18) 1600 (HR-20)
Overall dimensions (L x W x H)	1800 x 1700 x 1700	2100 x 1540 x 1500	1800 x 1500 x 1600

Heavy Duty Multi-blade Rip Saw

MODEL	HM14-6	HM14-2
Max. depth of cut	140mm	120mm
Max sawblade diameter	410mm (16")	360mm (14")
Useful length of sawblade bush	300mm	300mm
Width of feed chain	300mm	300mm
Power of saw motor	50HP (60HP, 75HP)	40HP, 50HP (60HP, 75HP)
Feed motor	3HP	3HP
Speed of saw arbor	3200RPM	3200RPM
Variable feed speed of chain	6.7~35 M/min	6.7~35 M/min
Net weight	2000kg	1830kg
Packing weight	2200kg	1980kg
Packing dimensions (L x W x H)	1850 x 1700 x 1700mm	1850 x 1550 x 1600mm

* Specifications and design characteristics are subject to change without prior notice.

HOLYTEK

HOLYTEK INDUSTRIAL CORP.

9F-1, NO. 400, SEC. 1, CHANG PING RD., TAICHUNG, TAIWAN, R.O.C.

TEL: 886-4-2245-2818 (REP.) FAX: 886-4-2243-6928

E-mail: holytek@ms13.hinet.net

http://www.holytek.com.tw

HOLYTEK

I SVERIGE AB

SE-512 91 Sexdrega

Tel +46 325 625547