

HOLYTEK

HWR-400 HORIZONTAL BAND SAW



HOLYTEK

HWR-400 HORIZONTAL BAND SAW



Air Loaded Pressure Roller

- Eliminating the conventional spring laded pressure rollers, this machine employs air loaded pressure rollers. Especially when cutting wood of various thicknesses, the air load saves time on adjusting pressure roller position while increasing operational convenience.
- Pressure roller are easily adjusted in the vertical directions to suit various wood thicknesses.
- Maximum pressing thickness is 200 mm.

Blade Tension

- Blade tension is controlled by hydraulic system, ensuring correct tension control at any time.
- Blade tension is indicated by a tension gauge.



SPECIFICATIONS

Maximum Material Size (W*H)-最大切削木材截面(寬*高)	16"x8"(400x200mm)
Distance From Blade To Conveyor-鋸帶至輸送帶距離	3/32"~10-5/8"(2~250mm)
Minimum Cut piece-可切削最小厚度	2mm
Saw Wheel Diameter-鋸輪直徑	32"(800mm) / 36"(915mm)
Saw Blade Length-鋸帶長度	231"(5860mm) / 238-1/2"(6060mm)
Saw Blade Width-鋸帶寬度	2" (50mm) / 3" (75mm) / 4" (100mm)
Saw Blade Speed-鋸帶速度	32m/s / 36m/s / Option Saw Wheel Inverter 17~34m/s
Conveyor Belt Sezes(WxL)-輸送帶尺寸	16"x165-1/2"(400x4200mm)
Feed Speed(Variable)-輸送速度(可調)	0~25M/min / 0~30 M/min
Conveyor Height From Floor-輸送帶到地面高度	37"(940mm)
Saw Wheel Motor-鋸輪馬達規格	25HP / 30HP / 40HP / Option Inverter
Blade Lift Servo Motor-鋸帶升降馬達	0.5HP
Feeding Motor-輸送馬達規格	2 HP with Inverter 含變頻
Dust Hood Outlet Diameter-吸塵套口徑	4"x2 (100mmx2)
Packing Dimensions-包裝尺寸	280X228X225cm
Machine Net Weight-機器淨重	1960 KG / 2050 KG
Machine Gross Weight-機器毛重	2160 KG / 2250 KG
Standard Packing -標準包裝	PALLET 底板包裝

* All specifications and design are subject to change without notice.