


Band Resaw

Pneumatic Power
Feeder for Added
Rigidity and Safety



HB-800

The heavy duty Band Resaw HB-800 is designed for high speed accurate resawing and application for timber merchants, joiners and other light resaw working. The most competitive price and many advanced features guarantee the best value for this Band Resaw machine. Auto feeding from power feeder increases working efficiency.

HOLYTEK

DESIGN FEATURES

- Specially designed Bakelite fitted on the blade guide assembly gives rigid, positive side support.
- All cast iron large table size: 1150 x 800mm. Maximum tilt of 45 degrees front downward for bevel cuts.
- Blade tension can be conveniently adjusted by means of a handwheel. A tension scale allows the operator to correctly adjust the tension for different blade widths.
- The cast iron flywheels are precision machined and dynamically balanced for smooth running.
- The see-through guard provides for the operator's safety and protection.
- The central control panel is equipped with manual star-delta switch overload protection and power feeder switch together.
- Foot brake permits the quick shutdown of machining operations.
- The blade lubrication is supplied from a large storage tank beyond the table.
- Equipped with a 100mm (4") wide sawblade and powerful 15HP motor.
- The unit can be equipped with mechanical or pneumatic power feeder, according to customer's preference.

SPECIFICATIONS

MODEL	HB-800
Saw flywheel dia.	800 mm (31 1/2")
Saw flywheel width	90 mm (3 1/2")
Table size	1150 x 800 mm (45 1/4" x 31 1/2")
Table height from floor	1000 mm (39 3/8")
Cutting capacity (height x width)	390 x 778 mm (by guide)
Length of sawblade	5515 mm
Sawblade linear speed	1800 mm/min (5900 ft/min)
Main motor	15 HP
N.W. / G.W.	800 / 1015 kgs
Machine size	1500 x 930 x 2420 mm
Packing size	2530 x 850 x 1410 mm

* All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.

HOLYTEK

I SVERIGE AB

SE-512 91 Sexdrega

Tel +46 325 625547

HOLYTEK

HOLYTEK INDUSTRIAL CORP.

9F-1, NO. 400, SEC. 1, CHANG PING RD., TAICHUNG, TAIWAN, R.O.C.

TEL: 886-4-2245-2818 (REP.) FAX: 886-4-2243-6928

E-mail: holytek@ms13.hinet.net

<http://www.holytek.com.tw>



BAND SAW POWER FEEDER

(Mechanical Type)

Eliminating the accidents that can occur with hand feeding and increasing the efficiency of straight cutting operations. The feed direction is reversible and the infinitely variable feed speed makes it possible to feed all types of wood for smooth cutting.

SPECIFICATIONS

MODEL	HF-150
Height of roll	150 mm
Diameter of roll	160 mm
Feed speed	5-20 mm/min
Motor	1 HP
N.W./G.W	90/110 kgs



Worm gear trunnion allows for effortless tilting of the large table.



1. Blade guide fixing knob
2. Blade guide raising handwheel
3. Blade track adjust knob
4. Blade tension handwheel
5. Blade tension indicator